

PATCHCORD DE FO

LABORATORIO



Fibra monomodo OS2
9/125 μ m
Color amarillo
Vaina de 2mm LSZH



Fibra monomodo
9/125 μ m
Exterior doble vaina
Color negro
Protección UV y LSZH
Vaina interna de 2 mm
Vaina externa 3 x 5 mm



Fibra multimodo OM1,
62,5/125 μ m
Color naranja
Vaina de 2 mm LSZH



Fibra multimodo OM2,
50/125 μ m
Color naranja
Vaina de 2 mm LSZH



Fibra multimodo OM3,
50/125 μ m
Color aqua
Vaina de 2 mm LSZH





Fibra multimodo OM4
50/125 μ m
Color fucsia
Vaina de 2 mm LSZH



ST



SC



LC



Fibra óptica plástica
1000 μ m
Color negro
Vaina de 2mm



ST/ BFOC



HFBR



Multipatchcord
Monomodo y Multimodo
Fibra interior / exterior
Vainas de 900 μ m o 2 mm



FC/PC




SC/PC



LC/PC



ST



FC/APC



SC/APC



LC/APC



E2000/APC

FIBRA SIMPLE Y DUPLEX

Tipo de Fibra	62,5/125 μ m	50/125 μ m	50/125 μ m	50/125 μ m	50/125 μ m
Nombre ISO	OM1	OM2	OM3	OM4	SM
Longitud de onda	850 / 1300 nm	850 / 1300 nm	850 / 1300 nm	850 / 1300 nm	1310 / 1490 / 1550 / etc
Atenuación máxima	3,10 / 1,00 dB/Km	3,10 / 1,00 dB/Km	3,10 / 1,00 dB/Km	3,10 / 1,00 dB/Km	3,10 / 1,00 dB/Km
Distancia a 1 GBit	500 mts	500 mts	600 mts	1000 mts	10 a 120 Km
Distancia a 10 GBit	30 mts	40 mts	300 mts	500 mts	10 a 120 Km